



3M™ Scott™ Vision 3 Positive Pressure Facemask



Description

The 3M™ Scott™ Vision 3 is offered in 4 different sizes and will accommodate a wide range of facial shapes and sizes. The facemasks are positive pressure and feature a Liquid Silicone Rubber outer mask with reflex seal and EDPM ori-nasal inner mask. The facemask visor is multi curvature and made of a scratch and impact resistant polycarbonate material with a flame retardant coating and provides excellent panoramic vision. The visor is held in place by two U-shaped clamps. The mask allows the wearer to wear integrated spectacle frames, without compromising the facemask seal. The facemask is available with either a five-point fully adjustable neoprene strap style harness, a two-point adjustable polyester or Kevlar® net style harnesses or a clamping system for many of the industries leading helmets.

The facemask features a left hand side bayonet connection for the demand valve. An option of an additional right quick-fit port is available to take a communications interface if required.

A speech diaphragm is mounted at the front of the mask to offer speech transmission and includes a low resistance positive pressure exhalation valve.

Applications

The Vision 3 is specifically designed for use with the 3M Scott range of breathing apparatus from the Professional Fire Fighting SCBA through to the Airline and escape breathing apparatus range. In conjunction with 3M Scott breathing apparatus it is suitable for providing respiratory protection for an Immediately Dangerous to Life or Health (IDLH) environment.

Maintenance/cleaning/servicing

Cleaning should only be carried out as specified in the user instructions. Maintenance and servicing must only be performed by trained personnel following the procedures in the service and maintenance manual.

Specification



Approvals

CE marked in accordance with EN 136:1998 Class III

CE marked in accordance with EN 137:2006 Type II when used in conjunction with approved 3M Scott SCBA

CE marked in accordance with EN 14593 when used with 3M™ Scott™ airline equipment

AS1716/NZ

Materials

Visor	Polycarbonate with silicone coating
Inhale valve flaps	Silicone rubber
Exhale valve flaps	Polyisoprene rubber
Exhale valve housing	Polyamide
Exhale valve spring	Stainless steel
Speech diaphragm	Mylar (polyester) film membrane in a moulded polyethylene grid with anodised aluminium coating
Visor surround	Polyamide 6-6
Outer mask	Injection moulded liquid silicone
Front cover	Glass filled polyamide
Demand valve port	Glass filled polyamide
Inner mask	Thermoplastic elastomer
Screws	Stainless steel
Nuts	Nickel plated brass
Buckles	Polyamide
Headharness	5 point neoprene, net head harness in polyester or Kevlar® material
Clamping system (optional)	Stainless steel brackets, plastic clamp mechanism
Packing specification	265×190×150m 0.75kg

3M Scott Fire & Safety

Pimbo Road
Skelmersdale
Lancashire, WN8 9RA
United Kingdom

Phone +44 (0)1695 711711
E-Mail skelmenq@mmm.com
Web www.3Mscott.com

ISO 9001 Registered. Please recycle. Printed in the UK. © 3M 2019. All rights reserved. 3M and Scott are trademarks of 3M Company. Kevlar is registered to DuPont. J460403

